
**Colour Multifunction Printer** 

MP C2004SP MP C2004ASP MP C2504SP MP C2504ASP








When you want an MFP that can carry your business and ensure it meets every workflow challenge, this range of multi-function printers will become your bedrock resource in any hard-working general office.

These flagship A3 colour MFPs are designed to cope with the high-intensity, high-output environment that helps your business thrive. So they offer increased reliability, high-quality production, and outstanding workplace efficiency – complemented by banner-print capabilities and features like the Smart Operation Panel.

- New: Single Pass Document Feeder so you save time and become even more efficient alongside the flexibility of two print speed options: 20 and 25ppm
- 10.1 inch Smart Operation Panel helps increase productivity and improves workflow with its Intuitive User Interface
- A Human Detection Sensor enables the MFP to jump into action as you approach so there's no time spent waiting
  for device warm-up





# Rich in functions, easy on energy.

### Access all areas.

Our 10.1 inch Smart Operation Panel offers an impressive touch and swipe interface so every command is intuitive and saves you time. Efficient document sharing and job-specific apps available from our dedicated Application Site – combine with extended software capabilities too. So you can integrate with our workflow enhancing technologies, meaning you can efficiently and securely access every feature available.



# Improved processor, increased productivity.

To help smooth your productivity and speed up jobs, these efficient, effective devices also boast a new, improved Intel processor. So it's not only greatly enhancing the printing and scanning of complex documents, but it's also reducing overall processing time and increasing customer productivity.

### More innovation.

Innovative technology helps to create a flexible office environment, and with several finisher options, including a booklet finisher, the automatic document reverse feeder (ARDF) and the newly introduced single pass document feeder (SPDF) come as standard. These finishers will streamline your workflow and allow you to produce professional documents again and again.

## Cut costs and save power.

With low TCO your spend is less – all while reducing your impact on the environment. And it's thanks in part to the energy saving Human Detection Sensor, which wakes up the device and makes it instantly available when you approach. The immediate warm-up is augmented by reduced power consumption in sleep mode, so costs are minimised when workflow is slower.



#### MP C2004SP/MP C2004ASP/MP C2504SP/MP C2504ASP

MAIN SPECIFICATIONS

#### **GENERAL**

Warm-up time: 25 seconds

First output speed: Full colour: 7.6/7.6/7.5/7.5 seconds

B/W: 5.4/5.4/5.3/5.3 seconds

Continuous output speed: Full colour: 20/20/25/25 pages per

minut

B/W: 20/20/25/25 pages per minute
CPU: Intel Atom Processor Bay Trail: 1.33

GHz

Memory: Standard: 2 GB Maximum: 4 GB

HDD: 250 GB

Dimensions (W x D x H): 587 x 685 x 788 mm

With ARDF: 587 x 685 x 913 mm With SPDF: 587 x 685 x 963 mm

Weight: 83.3 kg

Power source: 220 - 240 V, 50/60 Hz

**COPIER** 

Copying process: Dry Electrostatic Transfer System with

Dual component Development: 4-

Drum method

Multiple copying: Up to 999 copies Resolution: 600 dpi/4 bit

Zoom: From 25% to 400% in 1% steps

**PRINTER** 

Printer language: Standard: PCL5c, PCL6(XL), PDF Option: Adobe® PostScript® 3™,

XPS, PictBridge

Print resolution: Maximum (1,200 x 1,200 dpi/2bit)
Interface: Standard: SD slot LISB Host I/E

Standard: SD slot, USB Host I/F, Ethernet 10 base-T/100 base-TX/1000

base-T

Option: Wireless LAN (IEEE 802.11a/b/g/n), Bluetooth, USB Server for Second Network Interface, Bi-

directional IEEE 1284/ECP, USB 2.0 (Type B)

Windows® environments: Windows® Vista/7/8/8.1/10,

Windows® Server

2008/2008R2/2012/2012R2

Mac OS environments: Macintosh OS X Native v10.7 or later

UNIX environments:

UNIX Sun® Solaris SCO OpenServer

RedHat® Linux Enterprise

IBM® AIX

SAP® R/3® environments: SAP® R/3®

SCANNER

Scanning speed: ARDF: Max. 54 originals per minute

SPDF: Max. 110 (simplex)/180 (duplex) originals per minute

Resolution: Maximum: 1,200 dpi
Original size: A3, A4, A5, B4, B5
Bundled drivers: Network TWAIN
Scan to: E-mail, Folder

**FAX** 

Circuit: PSTN, PBX
Compatibility: ITU-T (CCITT) G3

Resolution: Standard: 8 x 3.85 line/mm, 200 x 100

dpi, 8 x 7.7 line/mm, 200 x 200 dpi Option: 8 x 15.4 line/mm, 400 x 400 dpi, 16 x 15.4 line/mm, 400 x 400 dpi

Compression method: MH, MR, MMR, JBIG

G3: 2 second(s) (200 x 100 dpi, JBIG), 3 second(s) (200 x 100 dpi, MMR)

Modem speed: Maximum: 33.6 Kbps

PAPER HANDLING

Transmission speed:

Recommended paper size:
Paper input capacity:

Paper output capacity:

SRA3, A3, A4, A5, A6, B4, B5, B6 Standard: 1,200 sheets

Maximum: 2,300 sheets Maximum: 1,625 sheets

Paper weight: 52 - 300 g/m<sup>2</sup>

**ECOLOGY** 

Power consumption: Maximum: 1,700 W

Ready mode: 46.5 W
Sleep mode: Less than 0.9 W
TEC (Typical Electricity Consumption):

0.7/0.7/0.9/0.9 kWh

**OPTIONS** 

ADF handle, 1 x 550-sheet paper tray, 2 x 550-sheet paper tray, Bridge unit, Internal finisher, Internal finisher with stapleless stapler, 1,000-sheet booklet finisher, Punch kits, Internal shift tray, One-bin tray, Side tray, Caster table, Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/b/g/n), Bluetooth, Pictbridge, PostScript3, Counter interface, File format converter, Key counter bracket, Card reader bracket, Data Overwrite Security Unit (Certified version), Fax Connection Unit, Fax marker, Fax memory, Fax option, Unicode Font Package for SAP, OCR Unit, SRA3 unit, XPS direct print, Enhanced security HDD, External keyboard bracket, NFC Card Reader, Banner paper tray guide, G3 Interface unit, Extended USB board, 4GB Memory unit

**CONSUMABLES** 

Toner target yield (A4/LT, 5% coverage):

Black: 15,000 prints Cyan: 9,500 prints Magenta: 9,500 prints Yellow: 9,500 prints

For availability of models, options and software, please consult your local supplier.

ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2016 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.



www.ricoh-europe.com